



---

# ARDEX P 60

## MULTIPRIMER

---

Improve adhesion to various substrates

For internal and external, walls and floors

Water based, no solvent hazard

Quick drying, apply subsequent products sooner

Low VOC content – meets Green Building Council of  
Australia Green Star IEQ-13 requirements



ARDEX HONGKONG LTD  
Unit D, 16/F, CNT Tower, No.338  
Hennessy Road,  
Wan Chai, Hong Kong  
TEL: 852-25296325  
FAX: 852-25298615

SH Office:  
ARDEX (SHANGHAI) CO., LTD  
4F, Building 2, No. 481,  
Guiping Rd.,  
Shanghai, China  
TEL: 86-21 64161800  
P.C.: 200233

# ARDEX P 60

## MULTIPRIMER

Edition: 2019-05-27

### DESCRIPTION

ARDEX P 60 is a water-based primer used for improving the adhesion of ARDEX products to various porous substrate. It is easy to apply with a sponge, brush or roller with applications of subsequent products able to take place with minimal downtime.

ARDEX P 60 is suitable for both internal and external, wall or floor applications.

### FOR USE WITH

ARDEX P 60 is compatible with subsequent applications of ARDEX tile adhesives, floor leveling compounds and under tile waterproofing membranes.

### SUBSTRATE

Medium density fiber-cement sheet,  
compressed fiber-cement sheet  
Jointing compound over plasterboard  
Concrete, renders, screeds  
Masonry and lightweight concrete blocks  
Autoclaved aerated concrete (AAC)  
Contact ARDEX if other substrates are not countered.

### SUBSTRATE PREPARATION

The surface to be primed must be clean, firm and free of dust, dirt, oil, grease, curing compounds, release agents and other barrier materials.

Ensure surfaces are dry prior to application, with no residue or permanent damp.

Surfaces must be suitable for the application of the subsequent product being used.

### APPLICATION

Shake contents and ARDEX P 60 is ready for use. Sponge, brush or roll ARDEX P 60 liberally over the entire surface to be sealed. For very porous surfaces a second coat of ARDEX P 60 is required, such as autoclaved aerated concrete.

All tools should be cleaned with water immediately after use.

### DRYING TIME

Ensure the ARDEX P 60 is fully dry prior to the application of subsequent products, allow approximately 15–30 minutes at 23°C and 50% relative humidity.

Type of substrate being primed, porosity and climatic conditions will affect drying times, allow longer for lower temperatures or high relative humidity.

### COVERAGE

One liter of ARDEX P 60 is sufficient for approximately 6m<sup>2</sup>, therefore the approximate coverage on each of the following units is :

20L---120 m<sup>2</sup>

4 L--- 24 m<sup>2</sup>

1 L--- 6 m<sup>2</sup>

Coverage will vary depending on the porosity of the surface and method of application.

### PACKAGING

ARDEX P 60 is packed in plastic pails-net volume 1L, 4L and 20L.

### SHELF LIFE

ARDEX P 60 has a shelf life of not less than 12 months when stored in the original unopened packaging, in a dry place at 23°C and 50% relative humidity.

Store away from direct sunlight. Replace lid tightly after use.

### ATTENTION

ARDEX P 60 is not suitable for use on glazed, impervious or silicone treated surfaces.

Metal surfaces must be primed with an appropriate metal primer.

Do not empty excess primer back into the original packaging as this may cause contamination of the contents.

### TECHNICAL DATA

Colour:	White
Mixing Ratio:	No mixing
Coverage:	Approx 6m <sup>2</sup> /litre
Drying Time:	Approx 15–30 min (at 23°C and 50% relative humidity)
pH:	8–9

### SAFETY PRECUATIONS

This product is considered non-hazardous and non-toxic in normal usage.

Avoid contact with skin and eyes; in case of contact with the eyes, rinse immediately with plenty of water and seek medical advice; wear suitable gloves and eye protection and keep the product out of the reach of children. If swallowed do not vomiting, give a glass of water and contact a doctor.

For further material safety data, consult the latest Material Safety Datasheet.

The technical details, recommendations and other information contained in this datasheet are given in good faith and represents the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable National or Local Standard, our instructions & recommendations, and only for the uses they are intended. Regional specific recommendations, standards, codes of practice, building regulations or industry guidelines may affect specific installation recommendations. Our Company policy is one of continuous Research & Development; we therefore reserve the right to update this information at any time without prior notice. We guarantee the consistent high quality of our products; however, as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof. The supply of our products and services is also subject to certain terms, warranties & exclusions; and these details will be made available to you on request. You should make yourself familiar with them.