



ARDEX AF 962

Carpet Adhesive

Low odour

Easy to use

Suitable for releasable application

Fast tack-off for rapid installation

Reliable bond with high coverage



ARDEX-QUICSEAL SINGAPORE PTE. LTD.

26 Tuas Ave 4 Singapore 639376

Telephone: +65 6861 7700

Fax: +65 6741 4666

Email: sales@ardex-quicseal.com

Website: www.ardex-quicseal.com

ARDEX AF 962

Carpet Adhesive

DESCRIPTION

Dispersion based, pressure sensitive adhesive which contains no hazardous solvents. ARDEX AF 962 provides superior tack and suitable for releasable carpet tiles installation.

ARDEX AF 962 is designed for internal installation of the below floor covering types.

- Vinyl-Backed Carpet Tiles
- Certain Carpet Pad/Cushion Underlay

FEATURES & BENEFITS

- Good plasticiser migration resistance
- No odour when dry
- Easy to use - for roller application
- Free of hazardous organic solvents
- Non-flammable

PRIMING

Priming is not required, however, on highly absorbent surfaces it can be advantageous to prime with ARDEX P 51 priming and bonding agent diluted 1:3 with cold, clean water. This will maintain the working time and ensure maximum coverage of the adhesive.

SUBSTRATE PREPARATION

Subfloors must be level, permanently dry, solid and free from cracks, dirt and adhesion-inhibiting substances. Apply corresponding ARDEX levelling compounds to non-absorbent and uneven subfloors.

APPLICATION

ARDEX AF 962 should be applied evenly to the suitably prepared substrate to obtain the recommended coverage as required for the relevant floor covering using a paint roller, brush, or flat edge trowel.

Avoid adhesive pools and spread evenly for optimum performance.

Allow the adhesive to 'set-up/tack-up' until dry to touch; approximately 30 - 60 minutes. When dry to touch, the adhesive will be tacky with no transfer to fingers or floor covering.

The set-up time will vary depending on job conditions, substrate, temperature and humidity. Cut, install and fit coverings within 24 hours ensuring that there has been no prior contamination of the adhesive. Roll the flooring in both directions using a recommended roller (normally 35 – 50kg). "The floor covering can then be re-positioned at any time".

TECHNICAL DATA

Raw material base:	Dispersion-based
Airing time:	approx. 15 min
Working time:	approx. 24 hours
Coverage Roller:	approx. 8 m ² /L
Cleaning agent:	warm with soapy water, before the adhesive starts to dry
Storage time:	12 months at room temperature

PACKAGING

ARDEX AF 962 is packed in a 20L plastic pail.

STORAGE

ARDEX AF 962 should not be stored in direct contact with sun and protected from freezing. When stored under the correct conditions and unopened, it has a shelf life of 12 months.

SAFETY PRECAUTIONS

ARDEX AF 962 is safe for normal use, but good hygiene should be practiced. Avoid skin contact; wash with soap and water before it dries. If it gets in your eyes, rinse thoroughly with water and seek medical advice. For ingestion, refer to the Safety Datasheet on www.ardex-quicseal.com and seek medical help.

DISCLAIMER

The technical datasheets are based on the latest information and given in good faith and represent the best of our knowledge and experience at

ARDEX AF 962

Carpet Adhesive

the time of printing. They are primarily offered for user's consideration and evaluation. It is the responsibility of the user to conduct their own tests to validate the suitability of the products. It is also the responsibility of the user to ensure that the products are used and handled correctly and in accordance with any applicable standards, the product instructions and recommendations and only for the uses they are intended. As we have no control over site conditions and the execution of the work, we accept no liability for any loss or damage which may rise as a result thereof. We also reserve the right to update the information at any time without prior notice to you to reflect our ongoing research and development program.

Offices:

Malaysia:

ARDEX QUICSEAL MALAYSIA SDN. BHD.
No. 72-2, Jalan Puteri 2/2, Bandar Puteri,
47100, Puchong, Selangor Darul Ehsan
Telephone: +603 8051 0311
Email: sales.malaysia@ardex-quicseal.com

Thailand:

ARDEX (THAILAND) CO., LTD
969 2nd Floor, Moo 13, Soi 45, Bangna-Trad Road
Bangkaew, Bangplee, Samutprakarn 10540 Thailand
Telephone: +66 2316 3069 Fax: +66 2316 3075
Email: sales@ardex.co.th
Website: www.ardex.co.th

Vietnam:

Mobile: +84 901 351 308
Email: sales@ardex-quicseal.com

MARCH 2025