



ARDEX F 230

Internal High Performance Skimcoat (Moisture Tolerant)

Advantages

- Firm and Durable
- Moisture & Mold-Resistant
- Good Workability
- Eco-Friendly Formulation



Description

ARDEX F 230 is formulated with selected fillers and pigments and blended with multiple high-quality additives. It develops high bond strength to the substrate and is easy to trowel.

Areas of Application

Suitable for fine levelling of interior wall surfaces that are prone to moisture. Allow to dry for 24 h before applying latex paint.

Substrate Preparation

The substrate must be sound and flat. Remove any remaining loose materials and contaminants; holes and cracks must be filled and repaired. The substrate must have adequate load-bearing capacity. It is recommended to use ARDEX F 200 Interior Basecoat Putty for coarse substrate levelling first.

ARDEX F 230

Internal High Performance Skimcoat (Moisture Tolerant)

Mixing

Pour clean water into a clean container, then add ARDEX F 230 powder, and immediately mix until a uniform, lump-free consistency is achieved.

Mechanical mixing is recommended. The mixing ratio by weight is: 20 kg ARDEX F 230 powder with approx. 8 L clean water. Adjust the water addition as appropriate according to actual conditions.

The above water dosage is based on tests carried out by our company at room temperature using standard mixing equipment; different mixers may affect the required water amount.

Application

Apply 2 coats with suitable tools on the prepared substrate to meet the flatness requirement. The first coat should be thicker and stiffer, with a thickness of approx. 0.5 mm–2 mm; the second coat should be thinner and more fluid. After the putty has dried and hardened, sand with sandpaper and remove dust. Make the surface smooth and flat. Application temperature: 5°C–40°C.

Packaging

20 kg/bag

Color

White

Standard

JG/T 298-2010 and JG/T 298-2026

Storage & Shelf Life

Shelf life 12 months when unopened and stored in a cool, dry place.

Health & Safety

Wear work clothing, gloves, and protective goggles during use.

After work, wash contacted areas with clean water and soap.

If the product accidentally splashes into the eyes, rinse immediately with plenty of clean water and seek medical attention.

Keep out of reach of pregnant women and children.

Ensure adequate ventilation during use.