



ARDEX F 240

Superior Jointing Compound

Advantages

- Excellent Flexibility
- High Strength & Crack Resistance
- Easy to Apply
- Eco-Friendly Formulation



Description

ARDEX F 240 is formulated with selected fillers and pigments and blended with multiple high-quality additives. It develops high bond strength to the substrate and is easy to trowel.

Areas of Application

Suitable for joint filling/patching of paper-faced gypsum board, cement fibre board, etc.
Can be used for filling wall holes, cable/conduit chases, nail holes, etc., and for localised levelling.

Substrate Preparation

Clean the substrate before application. Ensure the surface is dry, free of oil contamination and loose dust, and free of any looseness.

Mixing

Pour clean water into a clean container, then add ARDEX F 240 powder, and immediately mix until a uniform, lump-free consistency is achieved.

Mechanical mixing is recommended. The mixing ratio by weight is:

20 kg ARDEX F 240 powder with approx. 8 L clean water. Adjust the water addition as appropriate according to actual conditions. The above water dosage is based on tests carried out by our company at room temperature using standard mixing equipment; different mixers may affect the required water amount.

ARDEX F 240

Superior Jointing Compound

Application

Trowel-embed the mixed material into the joints, trowel smooth and level, and sand smooth after drying.

Notes

When used for full-surface skim application, keep the application thickness preferably below 2 mm;

Do not mix too much at one time. Use the mixed material before initial set; beyond the initial set time it will harden and must be discarded. For areas repaired/levelled too thick, apply in multiple passes.

Packaging

20 kg/bag

Color

White

Standard

JG/T 2075-2011

Technical Data

Application temperature	5–35°C
Interval between coats	2–4 hours (depending on site conditions)
Time to next procedure	2–3 days
Tensile strength	≥ 0.6 MPa

Storage & Shelf Life

Shelf life 12 months when unopened and stored in a cool, dry place.

Health & Safety

Wear work clothing, gloves, and protective goggles during use.

After work, wash contacted areas with clean water and soap.

If the product accidentally splashes into the eyes, rinse immediately with plenty of clean water and seek medical attention.

Keep out of reach of pregnant women and children.

Ensure adequate ventilation during use.