



ARDEX P 130

Wall & Floor Primer

Advantages

- High bond strength
- Excellent penetration
- Improves interfacial adhesion of the substrate
- Water-based formulation



Description

ARDEX P130 Wall & Floor Surface Consolidator is composed of polymer emulsion, additives, etc. It has excellent penetration and high bond strength, effectively improving substrate interfacial adhesion and enhancing application quality.

Areas of Application

Sealing and dust-binding of interior wall, ceiling and floor substrates, improving the adhesion performance of subsequent materials.

Substrate Preparation

The substrate surface must be dry, flat, sound, clean, free of oil contamination, dust, slurry residues and other pollutants, and also free of other loose attachments and substances detrimental to adhesion.

Application

Add 10–15% water appropriately according to the substrate condition and mix evenly. Apply directly to the substrate using a brush or roller. After it is completely dry through, proceed to the next procedure. On the primed interface, avoid using strongly alkaline materials as much as possible.

ARDEX P 130

Wall & Floor Primer

Consumption

Generally apply two coats. Theoretical consumption is 1.5–2 kg/10 m²; actual consumption may vary depending on substrate conditions and application method.

Packaging

18kg per pail

Color

Yellow or transparent

Storage & Shelf Life

Unopened and stored in a cool, dry place, the product has a shelf life of 12 months.

Standard

JC/T 907-2018

Safety Precautions

Under normal use, this product is non-toxic and harmless. However, avoid direct contact with skin and eyes. If it accidentally splashes into the eyes, rinse immediately with plenty of clean water and seek medical attention. Wear appropriate protective gloves and goggles correctly during use. If swallowed without vomiting, rinse mouth with water first, then drink as much water as possible and seek medical attention. Keep out of reach of children.