



ARDEX P 135

Substrate Enhancement Primer

Advantages

- Improve Bonding Strength
- Antifouling and Firm Dust
- Excellent penetration
- Water-based formulation



Description

ARDEX P135 Waterproofing Dedicated Primer is composed of polymer emulsion, synthetic binder, additives, etc. It has excellent penetration and high bond strength, effectively improving substrate interfacial adhesion and enhancing application quality.

Areas of Application

Sealing and dust-binding of interior wall and ceiling substrates, improving the bonding performance of waterproof coatings applied on concrete and brick masonry walls.

Substrate Preparation

The substrate surface must be dry, flat, sound, clean, free of oil contamination, dust, slurry residues and other pollutants, and also free of other loose attachments and substances detrimental to adhesion.

Application

Apply directly to the substrate using a brush or roller. For porous, dry and highly absorbent substrates, apply an additional coat after the first coat becomes surface-dry to achieve the best sealing/consolidation effect. After it is completely dry through, proceed to the next procedure.

ARDEX P 135

Substrate Enhancement Primer

Consumption

Generally apply two coats. Theoretical consumption is 1.5–2 kg/10m²; actual consumption may vary depending on substrate conditions and application method.

Packaging

7kg per pail

Color

Yellow

Storage & Shelf Life

Unopened and stored in a cool, dry place, the product has a shelf life of 12 months.

Standard

JC/T 907-2018

Safety Precautions

Keep away from children.

If in contact with skin, rinse immediately with plenty of clean water.

If swallowed, drink water immediately and seek medical assistance.

If it gets into the eyes, rinse immediately with water and seek medical assistance.