



# ARDEX P 60

## Multiprimer

### Advantages

- Improve adhesion to various substrates
- For internal and external, walls and floors
- Water based, no solvent hazard
- Quick drying, apply subsequent products sooner
- Low VOC content



### Description

ARDEX P 60 is a water-based primer used for improving the adhesion of ARDEX products to various porous substrate. It is easy to apply with a sponge, brush or roller with applications of subsequent products able to take place with minimal downtime. ARDEX P 60 is suitable for both internal and external, wall or floor applications.

### For use with

ARDEX P 60 is compatible with subsequent applications of ARDEX tile adhesives, floor leveling compounds and under tile waterproofing membranes.

### Substrate

Medium density fiber-cement sheet, compressed fiber-cement sheet  
Jointing compound over plasterboard  
Concrete, renders, screeds  
Masonry and lightweight concrete blocks  
Autoclaved aerated concrete (AAC)  
Contact ARDEX if other substrates are not countered.

### Substrate Preparation

The surface to be primed must be clean, firm and free of dust, dirt, oil, grease, curing compounds, release agents and other barrier materials.  
Ensure surfaces are dry prior to application, with no residue or permanent damp.  
Surfaces must be suitable for the application of the subsequent product being used.

# ARDEX P 60

## Multiprimer

### Application

Shake contents and ARDEX P 60 is ready for use. Sponge, brush or roll ARDEX P 60 liberally over the entire surface to be sealed. For very porous surfaces a second coat of ARDEX P 60 is required, such as autoclaved aerated concrete. All tools should be cleaned with water immediately after use.

### Drying Time

Ensure the ARDEX P 60 is fully dry prior to the application of subsequent products, allow approximately 15-30 minutes at 23°C and 50% relative humidity. Type of substrate being primed, porosity and climatic conditions will affect drying times, allow longer for lower temperatures or high relative humidity.

### Consumption

One liter of ARDEX P 60 is sufficient for approximately 6m<sup>2</sup>, Coverage will vary depending on the porosity of the surface and method of application.

### Packaging

5L per pail  
20L per pail

### Storage & Shelf Life

Unopened and stored in a cool, dry place, the product has a shelf life of 12 months.

### Attention

ARDEX P 60 is not suitable for use on glazed, impervious or silicone treated surfaces. Metal surfaces must be primed with an appropriate metal primer. Do not empty excess primer back into the original packaging as this may cause contamination of the contents.

### Technical Data

At 23°C and 50% relative humidity

Color	White
Mixing Ratio	No mixing
Consumption	Approx. 6m <sup>2</sup> /L
Drying Time	Approx. 15-30 min
pH	8-9

### Safety Precautions

This product is considered non-hazardous and non-toxic in normal usage.

Avoid contact with skin and eyes; in case of contact with the eyes, rinse immediately with plenty of water and seek medical advice; wear suitable gloves and eye protection and keep the product out of the reach of children. If swallowed do not vomit, give a glass of water and contact a doctor. For further material safety data, consult the latest Material Safety Datasheet.